

The Glowing Track 360 Suspension Casambi

Designed by FLOS Architectural, 2025




Suspension

360° suspended ambient lighting system that provides uniform light distribution. Available in three lengths (1200 mm, 1800 mm, and 2400 mm). Driver not included (Accessory kit for remote or surface driver).

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Suspension
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Top LED
Lamp category	LED
Number of lamps	1
Power (W)	38.3
Source flux (lm)	3696
System flux (lm)	2652
Efficacy (lm/W)	71

Physical

Color	Brushed Steel
Orientation	Fixed
Cord color	Transparent

Download

Family spec sheet	ZIP
Mounting instructions	PDF

Photometric Files


LDT / IES	ZIP
-----------	-----

Technical Drawings

2D	ZIP
3D	ZIP



Schematic light drawing



Ecodesign and Energy
Labelling



Replaceable (LED only)
light source by a
professional

Replaceable control
gear by a professional

Photometric

Lighting type	Total
Light distribution	Symmetric
CCT (K)	2200
CRI>	90
Rf fidelity index	87
Rg gamut index	104
LED Life / Failure Ratio	L80B10>72.000h_Tc65°C
Extreme cut off	No

Electrical

Forward voltage (V)	24
Driver	Remote
Dimmable	Yes
Dimming type	Dimmable Casambi
Dimming range (%)	1-100
Dimming interface	Remote Dimmable (Dimmer Not Included)
Batteries inside	No

Accessories & Power Supply



REQUIRED
Accessory

08.1063.14

Surface Canopy



REQUIRED
Power supply

08.1068.14

Ceiling Mounted Power Supply
Box for The Glowing Track 360
Suspension/Blind



REQUIRED
Power supply

08.1067.14

Ceiling Mounted Power Supply
Box for The Glowing Track
Suspension



REQUIRED
Power supply

08.1067.40

Ceiling Mounted Power Supply
Box for The Glowing Track
Suspension



REQUIRED
Power supply

08.1069.40

Ceiling Mounted Power Supply
Box for The Glowing Track 360
Suspension/Blind



REQUIRED
Accessory

08.1063.40

Surface Canopy



REQUIRED
Accessory

08.1064.14

Recessed Cover Plate



REQUIRED
Accessory

08.1064.40

Recessed Cover Plate



REQUIRED
Power supply

LEDSB96W24V-NDM-D1


LED Driver, 96W 24V Non-Dimmable



REQUIRED
Power supply

08.1068.40

Ceiling Mounted Power Supply Box for The Glowing Track 360 Suspension/Blind



REQUIRED
Accessory

08.1065.14

Mini Recessed Canopy



REQUIRED
Power supply

08.1069.14

Ceiling Mounted Power Supply Box for The Glowing Track 360 Suspension/Blind



REQUIRED
Accessory

08.1065.40

Mini Recessed Canopy



REQUIRED
Power supply

08.1066.40

Ceiling Mounted Power Supply Box for The Glowing Track Suspension



REQUIRED
Power supply

08.1066.14

Ceiling Mounted Power Supply Box for The Glowing Track Suspension



OPTIONAL
Connector

08.1206.ER

Corner Joint 2 Suspension/Surface



OPTIONAL
Connector

08.1207.ER

Corner Joint 3
Suspension/Surface



OPTIONAL
Connector

08.1208.ER

Corner Joint 4
Suspension/Surface



OPTIONAL
Connector

08.1213.ER

Linear Joint Suspension