

The Glowing Track 360 Vertical Dimmable 1-10V

Designed by FLOS Architectural, 2026

Ceiling

Surface lighting system with a vertical orientation that combines ambient lighting with a track that allows the installation of a wide range of projectors and accent lighting modules. Available in three lengths (600mm, 1200 mm, 1800 mm, and 2400 mm). Driver not included.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Ceiling
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Top LED
Number of lamps	1
Power (W)	12.4
System power (W)	13.8
Source flux (lm)	1232
System flux (lm)	762

Physical

Color	Black
Orientation	Fixed
Cord color	Transparent
IP internal	20



Download

- Family spec sheet

ZIP
- Mounting instructions

PDF

Photometric Files

- LDT / IES

ZIP

Technical Drawings

- 2D

ZIP
- 3D

ZIP



Ecodesign and Energy Labelling


LED

↔

LED

Replaceable (LED only) light source by a professional

Schematic light drawing



Photometric

Lighting type	Total
Light distribution	Symmetric
CCT (K)	2200
CRI>	90
McAdam steps (SDCM)	3
Rf fidelity index	93
Rg gamut index	100
LED Life / Failure Ratio	L80B10>72.000h_Tc65°C
Extreme cut off	No

Electrical

Insulation class	III
Forward voltage (V)	24
LED current (mA)	532
Driver	Remote
Dimmable	Yes
Dimming type	Dimmable 1-10V
Dimming range (%)	1-100
Dimming interface	Remote Dimmable (Dimmer Not Included)
Batteries inside	No

Accessories & Power Supply



REQUIRED
Power supply

LEDSB96W24V-NDM-D1
LED Driver, 96W 24V Non-Dimmable

OPTIONAL
Connector

08.1206.14
Corner Joint 2
Suspension/Surface