

## The Glowing Track 360 Vertical Dimmable Casambi

Designed by FLOS Architectural, 2025



Ceiling

360° surface ambient lighting system with a vertical orientation that provides uniform light distribution. Available in three lengths (1200 mm, 1800 mm, and 2400 mm). Driver not included.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Ceiling             |
| Environments           | Indoor dry location |
| Light Source Type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Top LED             |
| Lamp category          | LED                 |
| Number of lamps        | 1                   |
| Power (W)              | 37.2                |
| System power (W)       | 41.4                |
| Source flux (lm)       | 3696                |
| System flux (lm)       | 2652                |

### Physical

|             |                |
|-------------|----------------|
| Color       | Brushed Bronze |
| Orientation | Fixed          |
| Cord color  | Transparent    |
| IP internal | 20             |



### Download

- Family spec sheet
- Mounting instructions
- ZIP
- PDF

### Photometric Files


- LDT / IES
- ZIP

### Technical Drawings

- 2D
- 3D
- ZIP
- ZIP



Schematic light drawing



Photometric

|                          |                       |
|--------------------------|-----------------------|
| Lighting type            | Total                 |
| Light distribution       | Symmetric             |
| CCT (K)                  | 2200                  |
| CRI>                     | 90                    |
| McAdam steps (SDCM)      | 3                     |
| LED Life / Failure Ratio | L80B10>72.000h_Tc65°C |
| Extreme cut off          | No                    |
| UGRL                     | <19                   |

Electrical

|                   |                                       |
|-------------------|---------------------------------------|
| Insulation class  | III                                   |
| Driver            | Remote                                |
| Dimmable          | Yes                                   |
| Dimming type      | Dimmable Casambi                      |
| Dimming range (%) | 1-100                                 |
| Dimming interface | Remote Dimmable (Dimmer Not Included) |
| Batteries inside  | No                                    |

Accessories & Power Supply



REQUIRED  
Power supply

LEDSB96W24V-NDM-D1  
LED Driver, 96W 24V Non-Dimmable

OPTIONAL  
Connector

08.1206.ES  
Corner Joint 2  
Suspension/Surface