

## The Glowing Track 360 Vertical Dimmable Dali

Designed by FLOS Architectural, 2026

Ceiling

Surface lighting system with a vertical orientation that combines ambient lighting with a track that allows the installation of a wide range of projectors and accent lighting modules. Available in three lengths ( 600mm, 1200 mm, 1800 mm, and 2400 mm). Driver not included.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Ceiling             |
| Environments           | Indoor dry location |
| Light Source Type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Top LED             |
| Number of lamps        | 1                   |
| Power (W)              | 12.4                |
| System power (W)       | 13.8                |
| Source flux (lm)       | 1484                |
| System flux (lm)       | 917                 |

### Physical

|             |               |
|-------------|---------------|
| Color       | Brushed Steel |
| Orientation | Fixed         |
| Cord color  | Transparent   |
| IP internal | 20            |



### Download

- Family spec sheet [ZIP](#)
- Mounting instructions [PDF](#)

### Photometric Files

- LDT / IES [ZIP](#)

### Technical Drawings


- 2D [ZIP](#)
- 3D [ZIP](#)



### Ecodesign and Energy Labelling



### Schematic light drawing



## Photometric

|                          |                       |
|--------------------------|-----------------------|
| Lighting type            | Total                 |
| Light distribution       | Symmetric             |
| CCT (K)                  | 3000                  |
| CRI>                     | 90                    |
| McAdam steps (SDCM)      | 3                     |
| Rf fidelity index        | 92                    |
| Rg gamut index           | 89                    |
| LED Life / Failure Ratio | L80B10>72.000h_Tc65°C |
| Extreme cut off          | No                    |

## Electrical

|                     |                                          |
|---------------------|------------------------------------------|
| Insulation class    | III                                      |
| Forward voltage (V) | 24                                       |
| LED current (mA)    | 532                                      |
| Driver              | Remote                                   |
| Dimmable            | Yes                                      |
| Dimming type        | Dimmable DALI 2                          |
| Dimming range (%)   | 1-100                                    |
| Dimming interface   | Remote Dimmable<br>(Dimmer Not Included) |
| Batteries inside    | No                                       |

Accessories & Power Supply



REQUIRED  
Power supply

LEDSB96W24V-NDM-D1  
LED Driver, 96W 24V Non-Dimmable

OPTIONAL  
Connector

08.1206.ER  
Corner Joint 2  
Suspension/Surface