

The Glowing Track 360 Vertical Dimmable Phase Cut

Designed by FLOS Architectural, 2025



Ceiling

360° surface ambient lighting system with a vertical orientation that provides uniform light distribution. Available in three lengths (1200 mm, 1800 mm, and 2400 mm). Driver not included.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Ceiling
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Top LED
Lamp category	LED
Number of lamps	1
Power (W)	24.8
System power (W)	27.6
Source flux (lm)	2464
System flux (lm)	1768

Physical

Color	Brushed Steel
Orientation	Fixed
Cord color	Transparent
IP internal	20



Download

- Family spec sheet [ZIP](#)
- Mounting instructions [PDF](#)

Photometric Files


- LDT / IES [ZIP](#)

Technical Drawings

- 2D [ZIP](#)
- 3D [ZIP](#)



Schematic light drawing



Photometric

Lighting type	Total
Light distribution	Symmetric
CCT (K)	2200
CRI>	90
McAdam steps (SDCM)	3
LED Life / Failure Ratio	L80B10>72.000h_Tc65°C
Extreme cut off	No
UGRL	<19

Electrical

Insulation class	III
Driver	Remote
Dimmable	Yes
Dimming type	Mains Cut Dimming
Dimming range (%)	1-100
Dimming interface	Remote Dimmable (Dimmer Not Included)
Batteries inside	No

Accessories & Power Supply



REQUIRED
Power supply

LEDSB96W24V-NDM-D1
LED Driver, 96W 24V Non-Dimmable

OPTIONAL
Connector

08.1206.ER
Corner Joint 2
Suspension/Surface