

# FLOS

06.2666.ER Brushed Steel

## The Glowing Track Blind Surface Integrated Driver

Designed by FLOS Architectural, 2025




Length: 1210 - Surface

Surface electrified track designed for maximum versatility, allowing the installation of a wide range of projectors and accent lighting modules. Available in three lengths (1200 mm, 1800 mm, and 2400 mm). Driver included.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

Mounting	Surface
Environments	Indoor dry location
Lamp category	LED

### Physical

Colour	Brushed Steel
Orientation	Fixed
Length (mm)	1210
IP internal	20

### Download

Mounting instructions



### Ecodesign and Energy Labelling



Replaceable control gear by a professional

## Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Dimmable	Yes
Power supply type	Dimmable DALI 2
Dimming interface	Remote Dimmable (Dimmer Not Included)
Batteries inside	No

## Accessories & Power Supply



REQUIRED  
Accessory

Installation

08.1240.00

Ceiling fixing kit for Driver  
Integrated Versions



REQUIRED  
Accessory

Installation

08.1240.40

Ceiling fixing kit for Driver  
Integrated Versions



OPTIONAL  
Connector

08.1210.ER

Corner Joint 2 Surface Integrated  
Driver



OPTIONAL  
Connector

08.1211.ER

Corner Joint 3 Surface Integrated  
Driver



OPTIONAL  
Connector

08.1212.ER

Corner Joint 4 Surface Integrated  
Driver



OPTIONAL  
Connector

08.1209.ER

Linear Joint Surface Integrated  
Driver