

# FLOS

06.2666.ES Brushed Bronze

## The Glowing Track Blind Surface Integrated Driver

Designed by FLOS Architectural, 2025




Length: 1210 - Surface

Surface electrified track designed for maximum versatility, allowing the installation of a wide range of projectors and accent lighting modules. Available in three lengths (1200 mm, 1800 mm, and 2400 mm). Driver included.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

Mounting	Surface
Environments	Indoor dry location
Lamp category	LED

### Physical


Colour	Brushed Bronze
Orientation	Fixed
Length (mm)	1210
IP internal	20

### Download

Mounting instructions



### Ecodesign and Energy Labelling



Replaceable control gear by a professional



## Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Dimmable	Yes
Power supply type	Dimmable DALI 2
Dimming interface	Remote Dimmable (Dimmer Not Included)
Batteries inside	No

## Accessories & Power Supply



REQUIRED  
Accessory

Installation

08.1240.00

Ceiling fixing kit for Driver  
Integrated Versions



REQUIRED  
Accessory

Installation

08.1240.40

Ceiling fixing kit for Driver  
Integrated Versions



OPTIONAL  
Connector

08.1209.ES

Linear Joint Surface Integrated  
Driver



OPTIONAL  
Connector

08.1210.ES

Corner Joint 2 Surface Integrated  
Driver



OPTIONAL  
Connector

08.1211.ES

Corner Joint 3 Surface Integrated  
Driver



OPTIONAL  
Connector

08.1212.ES

Corner Joint 4 Surface Integrated  
Driver