

FLOS

06.2671.ES Brushed Bronze

The Glowing Track Blind Surface Integrated Driver

Designed by FLOS Architectural, 2025




Length: 2410 - Surface

Surface electrified track designed for maximum versatility, allowing the installation of a wide range of projectors and accent lighting modules. Available in three lengths (1200 mm, 1800 mm, and 2400 mm). Driver included.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

Mounting	Surface
Environments	Indoor dry location
Lamp category	LED

Physical

Colour	Brushed Bronze
Orientation	Fixed
Length (mm)	2410
IP internal	20

Download

[Mounting instructions](#)



Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Dimmable	Yes
Power supply type	Non Dimmable, Dimmable Casambi
Dimming interface	Remote Dimmable (Dimmer Not Included)
Batteries inside	No

Accessories & Power Supply



REQUIRED
Accessory

Installation

08.1240.00

Ceiling fixing kit for Driver
Integrated Versions



REQUIRED
Accessory

Installation

08.1240.40

Ceiling fixing kit for Driver
Integrated Versions



OPTIONAL
Connector

08.1209.ES

Linear Joint Surface Integrated
Driver



OPTIONAL
Connector

08.1210.ES

Corner Joint 2 Surface Integrated
Driver



OPTIONAL
Connector

08.1211.ES

Corner Joint 3 Surface Integrated
Driver



OPTIONAL
Connector

08.1212.ES

Corner Joint 4 Surface Integrated
Driver