

# FLOS

05.4510.ES.CB Brushed Bronze

## The Glowing Track Surface Integrated Driver

Designed by FLOS Architectural, 2025




Length: 1210 - Surface

Surface lighting system that combines ambient lighting with a track that allows the installation of a wide range of projectors and accent lighting modules. Available in three lengths (1200 mm, 1800 mm, and 2400 mm). Driver included.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

Mounting	Surface
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Top LED
Lamp category	LED
Number of lamps	1
Power (W)	24.8
System power (W)	27.6
Source flux (lm)	2824
Lumen Output (lm)	1746

### Physical

Colour	Brushed Bronze
Orientation	Fixed
Length (mm)	1210
IP internal	20

### Download

Mounting instructions [↓ PDF](#)

### Photometric Files

LDT / IES [↓ ZIP](#)

### Technical Drawings

2D [↓ ZIP](#)

3D [↓ ZIP](#)




### Ecodesign and Energy Labelling

 Replaceable (LED only) light source by a professional

 Replaceable control gear by a professional

## Schematic light drawing



### Photometric

Lighting type	Total
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
McAdam steps (SDCM)	3
Rf fidelity index	87
Rg gamut index	104
LED Life / Failure Ratio	L80B10>72.000h_Tc65°C

### Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Dimmable	Yes
Power supply type	Dimmable Casambi
Dimming range (%)	1-100
Dimming interface	Remote Dimmable (Dimmer Not Included)
Batteries inside	No

## Accessories & Power Supply



REQUIRED  
Accessory

Installation

08.1240.00

Ceiling fixing kit for Driver  
Integrated Versions



REQUIRED  
Accessory

Installation

08.1240.40

Ceiling fixing kit for Driver  
Integrated Versions



OPTIONAL  
Connector

08.1209.ES

Linear Joint Surface Integrated  
Driver



OPTIONAL  
Connector

08.1210.ES

Corner Joint 2 Surface Integrated  
Driver



OPTIONAL  
Connector

08.1211.ES

Corner Joint 3 Surface Integrated  
Driver



OPTIONAL  
Connector

08.1212.ES

Corner Joint 4 Surface Integrated  
Driver