

# FLOS

05.4501.ER.CB Brushed Steel

## The Glowing Track Suspension Casambi

Designed by FLOS Architectural, 2025




Length: 1210 - Suspension

Suspended lighting system that combines ambient lighting with a track that allows the installation of a wide range of projectors and accent lighting modules. Available in three lengths (1200 mm, 1800 mm, and 2400 mm). Driver not included (Accessory kit for remote or surface driver).

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

Mounting	Suspension
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Top LED
Lamp category	LED
Number of lamps	1
Power (W)	24.8
System power (W)	27.6
Source flux (lm)	2968
Lumen Output (lm)	1834

### Physical

Colour	Brushed Steel
Orientation	Fixed
Length (mm)	1210
Cord colour	Transparent
Cord length (mm)	3000
Package height (mm)	12
Package width (mm)	260
Package length (mm)	12
IP internal	20

### Download

Mounting instructions [↓ PDF](#)

### Photometric Files

LDT / IES [↓ ZIP](#)

### Technical Drawings

2D [↓ ZIP](#)


3D [↓ ZIP](#)



### Ecodesign and Energy Labelling



## Schematic light drawing



### Photometric

Lighting type	Total
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
McAdam steps (SDCM)	3
Rf fidelity index	92
Rg gamut index	89
LED Life / Failure Ratio	L80B10>72.000h_Tc65°C

### Electrical

Insulation class	III
Power supply	Remote
Dimmable	Yes
Power supply type	Dimmable Casambi
Dimming range (%)	1-100
Dimming interface	Remote Dimmable (Dimmer Not Included)
Batteries inside	No

## Accessories & Power Supply



REQUIRED  
Power supply

Electrical

06.0501.ER

Remote Power Supply Kit 120W



REQUIRED  
Power supply

Electrical

06.0508.ER

Remote Power Supply Kit 150W



REQUIRED  
Power supply

Electrical

06.0502.ER

Surface Power Supply Kit 150W  
500mm



REQUIRED  
Power supply

Electrical

06.0505.ER

Recessed Power Supply Kit 150W  
522mm



OPTIONAL  
Connector

08.1205.ER

Linear Joint Surface



OPTIONAL  
Connector

08.1206.ER

Corner Joint 2  
Suspension/Surface



OPTIONAL  
Connector

08.1207.ER

Corner Joint 3  
Suspension/Surface



OPTIONAL  
Connector

08.1208.ER

Corner Joint 4  
Suspension/Surface



OPTIONAL  
Connector

08.1213.ER

Linear Joint Suspension