

The Glowing Track Suspension Casambi

Designed by FLOS Architectural, 2025




Suspension

Suspended lighting system that combines ambient lighting with a track that allows the installation of a wide range of projectors and accent lighting modules. Available in three lengths (1200 mm, 1800 mm, and 2400 mm). Driver not included (Accessory kit for remote or surface driver).

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Suspension
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Top LED
Lamp category	LED
Number of lamps	1
Power (W)	25.5
Source flux (lm)	2968
System flux (lm)	1834
Efficacy (lm/W)	73

Physical

Color	Brushed Bronze
Orientation	Fixed
Cord color	Transparent

Download

Family spec sheet	ZIP
Mounting instructions	PDF

Photometric Files


LDT / IES	ZIP
-----------	-----

Technical Drawings

2D	ZIP
3D	ZIP



Schematic light drawing



Photometric

Lighting type	Total
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
Rf fidelity index	92
Rg gamut index	89
LED Life / Failure Ratio	L80B10>72.000h_Tc65°C
Extreme cut off	No

Electrical

Forward voltage (V)	24
Driver	Remote
Dimmable	Yes
Dimming type	Dimmable Casambi
Dimming range (%)	1-100
Dimming interface	Remote Dimmable (Dimmer Not Included)
Batteries inside	No

Ecodesign and Energy
Labelling



Replaceable (LED only)
light source by a
professional

Replaceable control
gear by a professional

Accessories & Power Supply



REQUIRED
Power supply
08.1067.14
Ceiling Mounted Power Supply
Box for The Glowing Track
Suspension



REQUIRED
Power supply
LEDSB96W24V-NDM-D1
LED Driver, 96W 24V Non-
Dimmable



REQUIRED
Accessory
08.1063.14
Surface Canopy



REQUIRED
Power supply
08.1069.14
Ceiling Mounted Power Supply
Box for The Glowing Track 360
Suspension/Blind



REQUIRED
Accessory
08.1063.40
Surface Canopy




REQUIRED
Power supply
08.1066.40
Ceiling Mounted Power Supply
Box for The Glowing Track
Suspension



REQUIRED
Accessory
08.1064.14
Recessed Cover Plate



REQUIRED
Accessory
08.1064.40
Recessed Cover Plate



REQUIRED
Accessory

08.1065.14


Mini Recessed Canopy



REQUIRED
Power supply

08.1067.40

Ceiling Mounted Power Supply
Box for The Glowing Track
Suspension



REQUIRED
Accessory

08.1065.40

Mini Recessed Canopy



REQUIRED
Power supply

08.1066.14

Ceiling Mounted Power Supply
Box for The Glowing Track
Suspension



REQUIRED
Power supply

08.1068.14

Ceiling Mounted Power Supply
Box for The Glowing Track 360
Suspension/Blind



REQUIRED
Power supply

08.1068.40

Ceiling Mounted Power Supply
Box for The Glowing Track 360
Suspension/Blind



REQUIRED
Power supply

08.1069.40

Ceiling Mounted Power Supply
Box for The Glowing Track 360
Suspension/Blind



OPTIONAL
Connector

08.1207.ES

Corner Joint 3
Suspension/Surface



OPTIONAL
Connector

08.1206.ES

Corner Joint 2
Suspension/Surface



OPTIONAL
Connector

08.1208.ES

Corner Joint 4
Suspension/Surface



OPTIONAL
Connector

08.1213.ES

Linear Joint Suspension