

## The Glowing Track Suspension Dimmable 1-10V

Designed by FLOS Architectural, 2025




### Suspension

Suspended lighting system that combines ambient lighting with a track that allows the installation of a wide range of projectors and accent lighting modules. Available in three lengths (1200 mm, 1800 mm, and 2400 mm). Driver not included (Accessory kit for remote or surface driver).

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Suspension          |
| Environments           | Indoor dry location |
| Light Source Type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Top LED             |
| Lamp category          | LED                 |
| Number of lamps        | 1                   |
| Power (W)              | 51.1                |
| Source flux (lm)       | 4928                |
| System flux (lm)       | 3047                |
| Efficacy (lm/W)        | 61                  |

### Physical

|             |             |
|-------------|-------------|
| Color       | White       |
| Orientation | Fixed       |
| Cord color  | Transparent |

### Download

|                       |     |
|-----------------------|-----|
| Family spec sheet     | ZIP |
| Mounting instructions | PDF |

### Photometric Files


|           |     |
|-----------|-----|
| LDT / IES | ZIP |
|-----------|-----|

### Technical Drawings

|    |     |
|----|-----|
| 2D | ZIP |
| 3D | ZIP |



Schematic light drawing



Photometric

|                          |                       |
|--------------------------|-----------------------|
| Lighting type            | Total                 |
| Light distribution       | Symmetric             |
| CCT (K)                  | 2200                  |
| CRI>                     | 90                    |
| Rf fidelity index        | 87                    |
| Rg gamut index           | 104                   |
| LED Life / Failure Ratio | L80B10>72.000h_Tc65°C |
| Extreme cut off          | No                    |

Electrical

|                     |                                       |
|---------------------|---------------------------------------|
| Forward voltage (V) | 24                                    |
| Driver              | Remote                                |
| Dimmable            | Yes                                   |
| Dimming type        | Dimmable 1-10V                        |
| Dimming range (%)   | 1-100                                 |
| Dimming interface   | Remote Dimmable (Dimmer Not Included) |
| Batteries inside    | No                                    |

Ecodesign and Energy Labelling



Replaceable (LED only) light source by a professional

Replaceable control gear by a professional

Accessories & Power Supply



REQUIRED  
Power supply  
LEDSB96W24V-NDM-D1  
LED Driver, 96W 24V Non-Dimmable



REQUIRED  
Accessory  
08.1063.40  
Surface Canopy



REQUIRED  
Accessory  
08.1064.40  
Recessed Cover Plate



REQUIRED  
Accessory  
08.1065.40  
Mini Recessed Canopy



REQUIRED  
Power supply  
08.1066.40  
Ceiling Mounted Power Supply Box for The Glowing Track Suspension



REQUIRED  
Power supply  
08.1067.40  
Ceiling Mounted Power Supply Box for The Glowing Track Suspension



REQUIRED  
Power supply  
08.1068.40  
Ceiling Mounted Power Supply Box for The Glowing Track 360 Suspension/Blind



REQUIRED  
Power supply  
08.1069.40  
Ceiling Mounted Power Supply Box for The Glowing Track 360 Suspension/Blind



OPTIONAL  
Connector

08.1206.40

Corner Joint 2  
Suspension/Surface



OPTIONAL  
Connector

08.1207.40

Corner Joint 3  
Suspension/Surface



OPTIONAL  
Connector

08.1208.40

Corner Joint 4  
Suspension/Surface



OPTIONAL  
Connector

08.1213.40

Linear Joint Suspension