

FLOS


05.4532.ER.CB Brushed Steel

The Glowing Track Vertical Casambi

Designed by FLOS Architectural, 2025

Length: 1810 - Ceiling

Surface lighting system with a vertical orientation that combines ambient lighting with a track that allows the installation of a wide range of projectors and accent lighting modules. Available in three lengths (600mm, 1200 mm, 1800 mm, and 2400 mm). Driver not included.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

Main specifications

| | |
|------------------------|---------------------|
| Mounting | Ceiling |
| Environments | Indoor dry location |
| Light source type | LED |
| Light sources included | Yes |
| LED type | Top LED |
| Lamp category | LED |
| Number of lamps | 1 |
| Power (W) | 37.2 |
| System power (W) | 41.4 |
| Source flux (lm) | 3696 |
| Lumen Output (lm) | 2619 |

Physical

| | |
|---------------------|---------------|
| Colour | Brushed Steel |
| Orientation | Fixed |
| Length (mm) | 1810 |
| Cord colour | Transparent |
| Package height (mm) | 12 |
| Package width (mm) | 260 |
| Package length (mm) | 12 |
| IP internal | 20 |

Download

Mounting instructions [↓ PDF](#)

Photometric Files

LDT / IES [↓ ZIP](#)

Technical Drawings

2D [↓ ZIP](#)


3D [↓ ZIP](#)

Ecodesign and Energy Labelling

 Replaceable (LED only) light source by a professional



Schematic light drawing



Photometric

| | |
|--------------------------|-----------------------|
| Lighting type | Total |
| Light distribution | Symmetric |
| CCT (K) | 2700 |
| CRI> | 90 |
| McAdam steps (SDCM) | 3 |
| Rf fidelity index | 87 |
| Rg gamut index | 104 |
| LED Life / Failure Ratio | L80B10>72.000h_Tc65°C |
| UGR _L | <16 |

Electrical

| | |
|-------------------|---------------------------------------|
| Insulation class | III |
| Power supply | Remote |
| Dimmable | Yes |
| Power supply type | Dimmable Casambi |
| Dimming range (%) | 1-100 |
| Dimming interface | Remote Dimmable (Dimmer Not Included) |
| Batteries inside | No |

Accessories & Power Supply



REQUIRED Power supply

Electrical

60.9777A

Remote Power Supply Non
Dimmable 24V. 120W. 220/240V

OPTIONAL Connector

08.1206.ER

Corner Joint 2
Suspension/Surface