

FLOS


05.4534.40.CB White

The Glowing Track Vertical Casambi

Designed by FLOS Architectural, 2025

Length: 2410 - Ceiling

Surface lighting system with a vertical orientation that combines ambient lighting with a track that allows the installation of a wide range of projectors and accent lighting modules. Available in three lengths (600mm, 1200 mm, 1800 mm, and 2400 mm). Driver not included.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Ceiling
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Top LED
Lamp category	LED
Number of lamps	1
Power (W)	49.6
System power (W)	55.2
Source flux (lm)	5648
Lumen Output (lm)	3492

Physical

Colour	White
Orientation	Fixed
Length (mm)	2410
Cord colour	Transparent
IP internal	20

Download

Mounting instructions [↓ PDF](#)

Photometric Files

LDT / IES [↓ ZIP](#)

Technical Drawings

2D [↓ ZIP](#)


3D [↓ ZIP](#)

Ecodesign and Energy Labelling

 Replaceable (LED only) light source by a professional



Schematic light drawing



Photometric

Lighting type	Total
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
McAdam steps (SDCM)	3
Rf fidelity index	87
Rg gamut index	104
LED Life / Failure Ratio	L80B10>72.000h_Tc65°C
UGR _L	<16

Electrical

Insulation class	III
Power supply	Remote
Dimmable	Yes
Power supply type	Dimmable Casambi
Dimming range (%)	1-100
Dimming interface	Remote Dimmable (Dimmer Not Included)
Batteries inside	No

Accessories & Power Supply



REQUIRED Power supply

Electrical

60.9777A

Remote Power Supply Non
Dimmable 24V. 120W. 220/240V

OPTIONAL Connector

08.1206.40

Corner Joint 2
Suspension/Surface