

# FLOS


05.4531.ER.DA Brushed Steel

## The Glowing Track Vertical Dali

Designed by FLOS Architectural, 2025

Length: 1210 - Ceiling

Surface lighting system with a vertical orientation that combines ambient lighting with a track that allows the installation of a wide range of projectors and accent lighting modules. Available in three lengths ( 600mm, 1200 mm, 1800 mm, and 2400 mm). Driver not included.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Ceiling             |
| Environments           | Indoor dry location |
| Light source type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Top LED             |
| Lamp category          | LED                 |
| Number of lamps        | 1                   |
| Power (W)              | 24.8                |
| System power (W)       | 27.6                |
| Source flux (lm)       | 2968                |
| Lumen Output (lm)      | 1834                |

### Physical

|             |               |
|-------------|---------------|
| Colour      | Brushed Steel |
| Orientation | Fixed         |
| Length (mm) | 1210          |
| Cord colour | Transparent   |
| IP internal | 20            |

### Download

[Mounting instructions](#) PDF

### Photometric Files

[LDT / IES](#) ZIP

### Technical Drawings

[2D](#) ZIP


[3D](#) ZIP

### Ecodesign and Energy Labelling

Replaceable (LED only) light source by a professional



## Schematic light drawing



### Photometric

|                          |                       |
|--------------------------|-----------------------|
| Lighting type            | Total                 |
| Light distribution       | Symmetric             |
| CCT (K)                  | 3000                  |
| CRI>                     | 90                    |
| McAdam steps (SDCM)      | 3                     |
| Rf fidelity index        | 92                    |
| Rg gamut index           | 89                    |
| LED Life / Failure Ratio | L80B10>72.000h_Tc65°C |
| UGR <sub>L</sub>         | <16                   |

### Electrical

|                   |                                       |
|-------------------|---------------------------------------|
| Insulation class  | III                                   |
| Power supply      | Remote                                |
| Dimmable          | Yes                                   |
| Power supply type | Dimmable DALI 2                       |
| Dimming range (%) | 1-100                                 |
| Dimming interface | Remote Dimmable (Dimmer Not Included) |
| Batteries inside  | No                                    |

## Accessories & Power Supply



### REQUIRED Power supply

Electrical

60.9777A

Remote Power Supply Non  
Dimmable 24V. 120W. 220/240V

### OPTIONAL Connector

08.1206.ER

Corner Joint 2  
Suspension/Surface