

The Glowing Track Vertical Dimmable Dali

Designed by FLOS Architectural, 2026

Ceiling

Surface lighting system with a vertical orientation that combines ambient lighting with a track that allows the installation of a wide range of projectors and accent lighting modules. Available in three lengths (600mm, 1200 mm, 1800 mm, and 2400 mm). Driver not included.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Ceiling
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Top LED
Number of lamps	1
Power (W)	12.4
System power (W)	13.8
Source flux (lm)	1412
System flux (lm)	873

Physical

Color	Brushed Steel
Orientation	Fixed
Cord color	Transparent
IP internal	20



Download

- Family spec sheet [ZIP](#)
- Mounting instructions [PDF](#)

Photometric Files

- LDT / IES [ZIP](#)

Technical Drawings


- 2D [ZIP](#)
- 3D [ZIP](#)



Ecodesign and Energy Labelling



Schematic light drawing



Photometric

Lighting type	Total
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
McAdam steps (SDCM)	3
Rf fidelity index	87
Rg gamut index	104
LED Life / Failure Ratio	L80B10>72.000h_Tc65°C
Extreme cut off	No

Electrical

Insulation class	III
Forward voltage (V)	24
LED current (mA)	532
Driver	Remote
Dimmable	Yes
Dimming type	Dimmable DALI 2
Dimming range (%)	1-100
Dimming interface	Remote Dimmable (Dimmer Not Included)
Batteries inside	No

Accessories & Power Supply



REQUIRED
Power supply

LEDSB96W24V-NDM-D1
LED Driver, 96W 24V Non-Dimmable

OPTIONAL
Connector

08.1206.ER
Corner Joint 2
Suspension/Surface