

The Running Magnet Recessed Feed Unit Profile


Designed by FLOS Architectural, 2015



'Electromechanical profile for recessed installation in plasterboard ceilings and walls.
Linear profiles available in two versions: power feed profiles for connecting to a driver, and intermediate profiles.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Wall recessed, Ceiling recessed
Environments	Indoor dry location
Light sources included	no

Physical

Colour	Black
Trim	No
Recessed depth (mm)	86
Length (mm)	2000
Net weight (kg)	6.60
IP internal	20
IP external	20

Download

Mounting instructions

ZIP



Electrical

Forward voltage (V)	24
Power supply	Remote excluded
Power supply type	Non Dimmable, Dimmable Casambi, Dimmable DALI 2

Notes

The Recessed version can only be installed on 12.5 mm thick plasterboard surfaces. Covers included with the power feed profiles. 90° corners available in the same plane (symmetrical element for left and right corners), symmetrical 90° inner and outer corners in different planes. For connection to the driver. Permanent or adjustable fastening kits available (optional). The fastening kits for the roof permit installing without using aluminium fastening profiles. Recommended for installations where the Running Magnet 2.0 cannot be installed before the suspended plasterboard ceiling (use 2 units).

Accessories & Power Supply



REQUIRED
Installation

08.8865.14A
Endcap. 2 unit kit



REQUIRED
Power supply
Electrical

60.9352
LED power supply source for remote installation in 24V/200W electric control panel. To avoid problems of overload it is recommended to install a power source every 185W. 100/240V.



REQUIRED
Power supply
Electrical

60.9089
Electronic transformer with constant voltage (24V) for LED. 100/240V. 60W



REQUIRED
Power supply
Electrical

60.9407
Electronic transformer with constant voltage (24V) for LED. 100/240V. 120W



OPTIONAL
Installation

08.8866.14
Fixed ceiling kit. 2 unit kit



OPTIONAL
Installation

08.8867.14
Adjustable ceiling kit. 2 unit kit



OPTIONAL
Electrical

06.1987.14
Multifunction Smart Device for Running Magnet & Fast Track



OPTIONAL
Electrical

06.1987.40
Multifunction Smart Device for Running Magnet & Fast Track