

## The Running Magnet Recessed Intermediate Profile

Designed by FLOS Architectural, 2015




Length: 2500 - Wall recessed, Ceiling recessed

'Electromechanical profile for recessed installation in plasterboard ceilings and walls. Linear profiles available in two versions: power feed profiles for connecting to a driver, and intermediate profiles.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



### Main specifications

|                        |                                 |
|------------------------|---------------------------------|
| Mounting               | Wall recessed, Ceiling recessed |
| Environments           | Indoor dry location             |
| Light sources included | no                              |

### Physical

|                     |       |
|---------------------|-------|
| Colour              | Black |
| Trim                | No    |
| Recessed depth (mm) | 86    |
| Length (mm)         | 2500  |
| Net weight (kg)     | 7.00  |
| IP internal         | 20    |
| IP external         | 20    |

### Download

Mounting instructions



### Electrical

Forward voltage (V) 24

## Notes

The Recessed version can only be installed on 12.5 mm thick plasterboard surfaces. Covers included with the power feed profiles. 90° corners available in the same plane (symmetrical element for left and right corners), symmetrical 90° inner and outer corners in different planes. Permanent or adjustable fastening kits available (optional). The fastening kits for the roof permit installing without using aluminium fastening profiles. Recommended for installations where the Running Magnet 2.0 cannot be installed before the suspended plasterboard ceiling (use 3 units).

---

Accessories & Power Supply



OPTIONAL  
ACCESSORYTYPE2

08.8867.14  
Adjustable ceiling kit. 2 unit kit



OPTIONAL  
ACCESSORYTYPE2

08.8866.14  
Fixed ceiling kit. 2 unit kit



OPTIONAL  
ACCESSORYTYPE2

08.8865.14A  
Endcap. 2 unit kit



OPTIONAL  
ACCESSORYTYPE1

06.1987.40  
Multifunction Smart Device for  
Running Magnet & Fast Track



OPTIONAL  
ACCESSORYTYPE1

06.1987.14  
Multifunction Smart Device for  
Running Magnet & Fast Track