

The Running Magnet Recessed Intermediate Profile

Designed by FLOS Architectural, 2015




Length: 3000 - Wall recessed, Ceiling recessed

'Electromechanical profile for recessed installation in plasterboard ceilings and walls. Linear profiles available in two versions: power feed profiles for connecting to a driver, and intermediate profiles.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Wall recessed, Ceiling recessed
Environments	Indoor dry location
Light sources included	no

Physical

Colour	Black
Trim	No
Recessed depth (mm)	86
Length (mm)	3000
Net weight (kg)	8.40
IP internal	20
IP external	20

Download

Mounting instructions



Photometric

Extreme cut off No

Electrical

Forward voltage (V) 24

Notes

The Recessed version can only be installed on 12.5 mm thick plasterboard surfaces. Covers included with the power feed profiles. 90° corners available in the same plane (symmetrical element for left and right corners), symmetrical 90° inner and outer corners in different planes. Permanent or adjustable fastening kits available (optional). The fastening kits for the roof permit installing without using aluminium fastening profiles. Recommended for installations where the Running Magnet 2.0 cannot be installed before the suspended plasterboard ceiling (use 4 units).

Accessories & Power Supply



OPTIONAL
ACCESSORYTYPE2

08.8867.14
Adjustable ceiling kit. 2 unit kit



OPTIONAL
ACCESSORYTYPE2

08.8866.14
Fixed ceiling kit. 2 unit kit



OPTIONAL
ACCESSORYTYPE2

08.8865.14A
Endcap. 2 unit kit



OPTIONAL
ACCESSORYTYPE1

06.1987.40
Multifunction Smart Device for
Running Magnet & Fast Track



OPTIONAL
ACCESSORYTYPE1

06.1987.14
Multifunction Smart Device for
Running Magnet & Fast Track