

The Running Magnet Surface Feed Unit Profile


Designed by FLOS Architectural, 2015



Electromechanical profile for surface-mounting. Linear profiles available in two versions: power feed profiles for connecting to a driver, and intermediate profiles.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Wall surface, Ceiling surface
Environments	Indoor dry location
Light sources included	no

Physical

Colour	White
Trim	No
Length (mm)	1000
Net weight (kg)	3.10
IP internal	20
IP external	20

Download

Mounting instructions

ZIP



Electrical

Forward voltage (V)	24
Power supply	Remote excluded
Power supply type	Non Dimmable, Dimmable Casambi, Dimmable DALI 2

Notes

Covers included with the power feed profiles. Attachment accessories included with all products.

90° corners available in the same plane (symmetrical element for left and right corner) and 90° symmetrical internal corners in a different plane, for the Surface and Down versions. For connection to the driver.

The inner part of the profile is always supplied in black.

Accessories & Power Supply



REQUIRED
Installation

08.8887.14A
Endcap. 2 unit kit



REQUIRED
Power supply
Electrical

60.9352
LED power supply source for remote installation in 24V/200W electric control panel. To avoid problems of overload it is recommended to install a power source every 185W. 100/240V.



REQUIRED
Power supply
Electrical

60.9089
Electronic transformer with constant voltage (24V) for LED. 100/240V. 60W



REQUIRED
Power supply
Electrical

60.9407
Electronic transformer with constant voltage (24V) for LED. 100/240V. 120W



OPTIONAL
Electrical

06.1987.40
Multifunction Smart Device for Running Magnet & Fast Track



OPTIONAL
Control interface
Electrical

60.9678A
LED module Dali/Push dimmable control unit for 12, 24 or 48Vdc