

The Running Magnet Suspension Down Feed Unit Profile

Designed by FLOS Architectural



Length: 59.05 - Suspension

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Suspension
Power (W)	100

Physical

Color	White
Length (in)	59.05
Net weight (lb)	9.27
Gross weight (lb)	10.92
Package volume (in)	2686
IP internal	20



Download


- Family spec sheet  ZIP
- Mounting instructions  PDF



Electrical

Insulation class	II
Forward voltage (V)	24
Driver	Remote

Accessories & Power Supply



REQUIRED
Electrical

08.8886.40
Surface power supply for direct and indirect lighting with housing for the driver



REQUIRED
Installation

08.8887.40A
Endcap. 2 unit kit



REQUIRED
Power supply
Electrical

LEDSB30W24V-NDM-D01
LED Driver, 24VDC, 30W, Non-Dimming, 120-277V



REQUIRED
Power supply
Electrical

LEDSB60W24V-NDM-D01
LED Driver, 24VDC, 60W, Non-Dimming, 120-277V




REQUIRED
Power supply

LEDSB96W24V-NDM-D01
LED Driver, 24VDC, 96W, Non-Dimming, 120-277V




OPTIONAL
Accessory
08.8883.40A
Canopy surface White, Power Supply not included order separately




OPTIONAL
Power supply
Electrical

08U0002.30A1V
Surface mount canopy 1/10V Dimmable



OPTIONAL
Power supply
Electrical

08U0002.30
Surface mount canopy Non Dimmable



OPTIONAL
Power supply

Electrical

08.0613.14A

Dimmable control box 1-10V,
24/48V. For remote installation.



OPTIONAL
Accessory

Installation

60.3097.11

1 m suspension rod with ceiling
rose with m6 thread



OPTIONAL
Corner

06.1657.40

90° Corner