

The Running Magnet Suspension Down Feed Unit Profile

Designed by FLOS Architectural



Length: 98.42 - Suspension

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Suspension
Power (W)	100

Physical

Color	Black
Length (in)	98.42
Net weight (lb)	15.44
Gross weight (lb)	18.2
Package volume (in)	4455
IP internal	20



Download

- Family spec sheet
- Mounting instructions
- ZIP

PDF



Electrical

Insulation class	II
Forward voltage (V)	24
Driver	Remote

Accessories & Power Supply



REQUIRED
Installation

08.8887.14A
Endcap. 2 unit kit



REQUIRED
Power supply
LEDSB96W24V-NDM-D01
LED Driver, 24VDC, 96W, Non-Dimming, 120-277V



REQUIRED
Power supply
Electrical
LEDSB60W24V-NDM-D01
LED Driver, 24VDC, 60W, Non-Dimming, 120-277V




REQUIRED
Power supply
Electrical
LEDSB30W24V-NDM-D01
LED Driver, 24VDC, 30W, Non-Dimming, 120-277V




OPTIONAL
Corner
06.1610.14
90° Corner. Can be powered




OPTIONAL
Accessory
08.8883.14A
Canopy surface Black, Power Supply not included order separately



OPTIONAL
Power supply
Electrical
08U0002.14
Surface mount canopy Non Dimmable



OPTIONAL
Power supply
Electrical
08U0002.14A1V
Surface mount canopy 1/10V Dimmable



OPTIONAL
Power supply

Electrical

08.0613.14A

Dimmable control box 1-10V,
24/48V. For remote installation.



OPTIONAL
Accessory

Installation

60.3097.14

1 m suspension rod extension set
with m6 thread



OPTIONAL
Corner

06.1657.14

90° Corner