

The Running Magnet Suspension Down Intermediate Profile

Designed by FLOS Architectural, 2015



Length: 3000 - Suspension

Electromechanical profile for suspended installations. Linear profiles available in two versions: power feed profiles for connecting to a driver, and intermediate profiles.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Suspension
Environments	Indoor dry location
Light sources included	no

Physical

Colour	White
Trim	No
Length (mm)	3000
Net weight (kg)	6.90
IP internal	20
IP external	20



Download

Mounting instructions	Download PDF
Mounting instructions	Download PDF



Electrical

Forward voltage (V) 24

Notes

Covers included with the power feed profiles.

Ceiling connection (4.2 m feed cable) and suspension (4 m steel cable) accessories included in all linear feed or intermediate products.

90° corners in the same plane (symmetrical element for right and left corners) for the Surface and Down versions. Provided for connection to the driver.

The inner part of the profile is always supplied in black.

Accessories & Power Supply



OPTIONAL
ACCESSORYTYPE2

08.8887.40A

Endcap. 2 unit kit



OPTIONAL
ACCESSORYTYPE1

06.1987.40

Multifunction Smart Device for
Running Magnet & Fast Track