

The Running Magnet Suspension Up&Down Feed Unit Profile

Designed by FLOS Architectural



Length: 78.74 - Suspension

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Suspension
Light Source Type	LED
Light sources included	Yes
LED type	Top LED
Power (W)	100
System flux (lm)	1688

Physical

Color	Black
Orientation	Fixed
Length (in)	78.74
Net weight (lb)	12.79
Gross weight (lb)	15
Package volume (in)	3601
IP internal	20



Download

- Family spec sheet [ZIP](#)
- Mounting instructions [PDF](#)

Photometric Files


- LDT / IES [ZIP](#)

Technical Drawings

- 2D [ZIP](#)
- 3D [ZIP](#)



Schematic light drawing



Photometric

Lighting type	Indirect
Light distribution	Symmetric
CCT (K)	3000
Beam angle C0-180 (°)	91
UGR _L	<10

Electrical

Insulation class	II
Forward voltage (V)	24
Driver	Remote

Accessories & Power Supply



REQUIRED

Installation

08.8887.14A

Endcap. 2 unit kit



OPTIONAL

Accessory

08.8883.14A

Canopy surface Black, Power
Supply not included order
separately