

## The Running Magnet Suspension Up&Down Feed Unit Profile

Designed by FLOS Architectural



Length: 78.74 - Suspension

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

### Main specifications

|                        |            |
|------------------------|------------|
| Mounting               | Suspension |
| Light Source Type      | LED        |
| Light sources included | Yes        |
| LED type               | Top LED    |
| Power (W)              | 100        |
| System flux (lm)       | 1688       |

### Physical

|                     |       |
|---------------------|-------|
| Color               | White |
| Orientation         | Fixed |
| Length (in)         | 78.74 |
| Net weight (lb)     | 12.79 |
| Gross weight (lb)   | 15    |
| Package volume (in) | 3601  |
| IP internal         | 20    |



### Download

- Family spec sheet [ZIP](#)
- Mounting instructions [PDF](#)

### Photometric Files


- LDT / IES [ZIP](#)

### Technical Drawings

- 2D [ZIP](#)
- 3D [ZIP](#)



### Schematic light drawing




Photometric

|                       |           |
|-----------------------|-----------|
| Lighting type         | Indirect  |
| Light distribution    | Symmetric |
| CCT (K)               | 3000      |
| Beam angle C0-180 (°) | 91        |
| UGR <sub>L</sub>      | <10       |

Electrical

|                     |        |
|---------------------|--------|
| Insulation class    | II     |
| Forward voltage (V) | 24     |
| Driver              | Remote |

Accessories & Power Supply




REQUIRED  
Electrical

08.8886.40  
Surface power supply for direct and indirect lighting with housing for the driver



REQUIRED  
Installation

08.8887.40A  
Endcap. 2 unit kit



OPTIONAL  
Accessory

08.8883.40A  
Canopy surface White, Power  
Supply not included order separately