

The Running Magnet Suspension Up&Down Intermediate Profile

Designed by FLOS Architectural



Length: 98.42 - Suspension

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications


Mounting	Suspension
Light Source Type	LED
Light sources included	Yes
LED type	Top LED
Power (W)	100
System flux (lm)	2109

Physical

Color	Black
Orientation	Fixed
Length (in)	98.42
Net weight (lb)	13.23
Package volume (in)	4455
IP internal	20



Schematic light drawing



Beam Angle:	91°	
h(m)	E(lx)	D(m)
1	910	2.05
2	227	4.10
3	101	6.15
4	57	8.20
5	36	10.25

Download

Family spec sheet [ZIP](#)
Mounting instructions [PDF](#)

Photometric Files

LDT / IES [ZIP](#)

Technical Drawings

2D [ZIP](#)
3D [ZIP](#)

Photometric

Lighting type	Indirect
Light distribution	Symmetric
CCT (K)	3000
Beam angle C0-180 (°)	91
UGR _L	<10

Electrical

Insulation class	II
Forward voltage (V)	24
Driver	Remote

Accessories & Power Supply



OPTIONAL

Installation

08.8887.14A

Endcap. 2 unit kit