

The Running Magnet Suspension Up&Down Intermediate Profile

Designed by FLOS Architectural, 2015




Length: 3000 - Suspension

'Electromechanical profile for suspended installations. Linear elements in the Up&Down version include indirect LED illumination in the upper part of the profile. Shared or separate power feed. Linear profiles available in two versions: power feed profiles for connecting to a driver, and intermediate profiles.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Suspension
Environments	Indoor dry location
Light sources included	no
LED type	Top LED
Lamp category	LED
Power (W)	25.2
System power (W)	26.8
Source flux (lm)	2531.34
Lumen Output (lm)	2531
Efficacy (lm/W)	94.44

Physical

Colour	Black
Trim	No
Length (mm)	3000
Net weight (kg)	7.20
IP internal	20
IP external	20

Download

Mounting instructions [↓ PDF](#)

Photometric Files

LDT / IES [↓ ZIP](#)

Technical Drawings


2D [↓ ZIP](#)

3D [↓ ZIP](#)

[Bim](#) [↓ ZIP](#)



Schematic light drawing



Photometric

Lighting type	Indirect
Light distribution	Asymmetric
CCT (K)	3000
CRI>	90
LED Life / Failure Ratio	L80B50 > 50.000h (Tc=85°C)
Beam angle C0-180 (°)	98
Beam angle C90-270 (°)	91
UGRL	<10

Electrical

Insulation class	III
Forward voltage (V)	24

Notes

Covers included with the power feed profiles. Ceiling connection (4.2 m feed cable) and suspension (4m steel cable) accessories included in all linear feed or intermediate products. 90° corners in the same plane (symmetrical element for right and left corners). Not provided for connection to the driver. The corners of the Suspended Running Magnet versions are not fitted with indirect illumination. Indirect illumination can be managed as a separate circuit if powered by a dedicated driver and, in the case of the DALI installation,if equipped with a dedicated optional DALI controller. To be ordered separately. Profiles cannot be cut. The inner part of the profile is always supplied in black.

Accessories & Power Supply



OPTIONAL
ACCESSORYTYPE2

08.8887.14A

Endcap. 2 unit kit



OPTIONAL
ACCESSORYTYPE1

06.1987.14

Multifunction Smart Device for
Running Magnet & Fast Track