

The Tracking Magnet Surface/Suspension Profile 90° Mechanical Corner


Designed by FLOS Architectural, 2017



Electromechanical profile for surface-mounting, available in lengths from 1m to 3m.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

Mounting	Suspension, Ceiling surface
Environments	Indoor dry location
Light sources included	no

Physical

Colour	Polished Aluminium
Trim	No
Field cuttable	No
Length (mm)	55
Net weight (kg)	0.14
IP internal	20
IP external	20

Download

[Mounting instructions](#)

[PDF](#)



Photometric

Extreme cut off	No
-----------------	----


Electrical

Forward voltage (V)	48
Emergency	No

Notes

90° mechanical corner. To create electrical continuity, order with the flexible intermediate connector.

Accessories & Power Supply



REQUIRED
Accessory

Electrical

06.0157.00
4-pole, 0.75 mm² section, 4-meter long, transparent power cable




REQUIRED
Accessory

06.5017.05
The Tracking Magnet Surface/Suspension Profile End Caps




REQUIRED
Accessory

08.0614.14
The Tracking Magnet Profile Intermediate Connector Flexible/Electrical Corner



REQUIRED
Accessory

Installation
08.0615.00
Ceiling fixing kit



REQUIRED
Accessory

Installation

08.0616.00
Ceiling fixing kit



REQUIRED
Accessory

Installation
08.8634.00
4m suspension steel cable



REQUIRED
Accessory

08.8883.14A
Canopy surface Black, Power Supply not included order separately



REQUIRED
Accessory

08.8883.40A
Canopy surface White, Power Supply not included order separately



REQUIRED

Electrical

08.8889.14

Recessed power supply rose



REQUIRED

Electrical

08.8889.40

Recessed power supply rose



REQUIRED

Accessory

Installation

60.3097.11

1 m suspension rod with ceiling
rose with m6 thread



REQUIRED

Accessory

Installation

60.3097.14

1 m suspension rod extension set
with m6 thread



REQUIRED

Control interface

Electrical

60.9395

LED module 1/10V dimmable
control unit for 12 to 48V
equipment.



REQUIRED

Electrical

06.1988.14

Multifunction Smart Device for
Tracking Magnet & Infra-Structure



REQUIRED

Electrical

06.1988.40

Multifunction Smart Device for
Tracking Magnet & Infra-Structure



REQUIRED

Control interface

Electrical

60.9678A

LED module Dali/Push dimmable
control unit for 12, 24 or 48Vdc