

FLOS



06.5070.05A Polished Aluminium

The Tracking Magnet Suspension Up&Down Profile Casambi / On Board Dimmer compatible

Designed by FLOS Architectural, 2018



Electrical/mechanical profile for suspended installations.

Are you a professional and your project needs
consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Suspension
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Top LED
Lamp category	LED
Number of lamps	1
Power (W)	6.5
System power (W)	6.8
Source flux (lm)	665.36
Lumen Output (lm)	419
Efficacy (lm/W)	61.62

Physical

Colour	Polished Aluminium
Trim	No
Field cuttable	No
Length (mm)	1000
Net weight (kg)	1.4
IP internal	20
IP external	20



Download

Mounting instructions  ZIP

Photometric Files

LDT / IES  ZIP


Technical Drawings

2D  ZIP

3D  ZIP



Schematic light drawing



Photometric

Lighting type	Indirect
Light distribution	Asymmetric
CCT (K)	3000
CRI>	90
McAdam steps (SDCM)	2
LED Life / Failure Ratio	L80B50 > 50.000h (Tc=85°C)
Beam angle C0-180 (°)	81
Beam angle C90-270 (°)	96
Extreme cut off	No
UGR _L	<10

Electrical

Insulation class	III
Forward voltage (V)	48
LED current (mA)	140
Power supply	Remote
Dimmable	Yes
Power supply type	Non Dimmable, Dimmable
Emergency	No

Notes

The linear elements in the Up&Down version include indirect LED lighting in the upper part of the profile. The magnetic profile and the Up lighting must be powered with the same equipment. Version compatible with "On board dimmer" luminaries and version compatible with system controlled luminaries (DALI, 1-10V, FLOS SMART CONTROL) available. Corners, connectors and accessories common for the two profile versions. Both versions have lengths of 1m-3m. The profiles cannot be cut. The covers must be ordered separately. 3m power cable included in all the linear power products. Suspension accessories (steel cable and rods) should be ordered separately. 90° corners available in the same plan (symmetrical element for left and right corners), common in Up&Down and Down versions. Not provided for connection to driver. The corners of the Suspended versions of Tracking Magnet do not have indirect lighting. Indirect lighting is controlled with a common circuit to the direct lighting.

Accessories & Power Supply



REQUIRED
Power supply
Electrical

60.9607
LED power supply source for remote installation, 110Vac-150W / 220Vac-200W




REQUIRED
Power supply
Electrical

60.9170
LED power supply source for remote installation, 48V/120W. 220/240 Vac



REQUIRED
Electrical

06.1988.40
Multifunction Smart Device for Tracking Magnet & Infra-Structure




REQUIRED
Power supply
Electrical

08.0632.14A
Surface power supply with driver included 320W / 48Vdc. DALI / No dim.



REQUIRED
Power supply
Electrical

60.8919
LED Power Supply Source for remote installation. 48V/320W. 100/240 Vac



REQUIRED
Power supply
Electrical

08.0631.14A
Surface power supply with driver included 320W / 48Vdc. 1-10V / 0-10V / No dim.




REQUIRED
Accessory
Installation

60.3097.11
1 m suspension rod with ceiling rose with m6 thread



REQUIRED
Accessory

08.8883.40A
Canopy surface White, Power Supply not included order separately



REQUIRED
Accessory

08.8883.14A

Canopy surface Black, Power Supply not included order separately




REQUIRED
Accessory

Electrical

08.0626.00

Power connector



REQUIRED
Power supply

Electrical

08.0631.40A

Surface power supply with driver included 320W / 48Vdc. 1-10V / 0-10V / No dim.



REQUIRED
Accessory

Electrical

08.0612.14

The Tracking Magnet Profile Intermediate Connector Straight



REQUIRED
Accessory

06.5026.05


The Tracking Magnet Suspension Up&Down Profile End Caps



REQUIRED
Electrical

08.8889.40

Recessed power supply rose



REQUIRED
Accessory

Installation

08.0627.00

Intermediate suspension kit for joining profiles



REQUIRED
Control interface

Electrical


60.9395

LED module 1/10V dimmable control unit for 12 to 48V equipment.



REQUIRED
Electrical

06.1988.14
Multifunction Smart Device for
Tracking Magnet & Infra-Structure



REQUIRED
Power supply
Electrical

08.0632.40A
Surface power supply with driver
included 320W / 48Vdc. DALI / No
dim.



REQUIRED
Accessory
Installation

60.3097.14
1 m suspension rod extension set
with m6 thread



REQUIRED
Electrical

08.8889.14
Recessed power supply rose



REQUIRED
Control interface
Electrical

60.9678A
LED module Dali/Push dimmable
control unit for 12, 24 or 48Vdc



REQUIRED
Accessory
Installation

08.8634.00
4m suspension steel cable