

# FLOS

09.3310.72C Grey

## Theblockoflight

Designed by Knud Holscher, 2015


LED - Power LED - 2.2W - 50lm - 3000K - CRI> 80 - Beam° 45



Semi-recessed signalling lamp for indoor or outdoor use. Non-regulable 100-240V, 50-60Hz power supply and 500 mm power cable included.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

Mounting	Wall recessed
Environments	Indoor dry location, Outdoor wet location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Lamp category	LED
Power (W)	2.2
Source flux (lm)	296
Lumen Output (lm)	50

### Physical

Colour	Grey
Trim	No
Orientation	Fixed
Recessed depth (mm)	47
Length (mm)	75
Net weight (kg)	0.4
IP internal	65

### Download

Mounting instructions [↓ PDF](#)

### Photometric Files

LDT / IES [↓ ZIP](#)


### Technical Drawings

2D [↓ ZIP](#)

3D [↓ ZIP](#)



## Schematic light drawing



Beam Angle: 45°

h(m)	E(lx)	D(m)
1	6	1.85
2	2	3.70
3	1	5.55
4	0	7.40
5	0	9.25

Luminous flux luminaire  
50 lm

### Photometric

Lighting type	Direct, Indirect
Light distribution	Asymmetric
CCT (K)	3000
CRI>	80
Beam angle C0-180 (°)	45
Beam angle C90-270 (°)	58
Extreme cut off	No
UGR <sub>L</sub>	<16

### Electrical

Insulation class	I
Frequency (Hz)	50/60
Power supply	Integrated
Dimmable	No
Power supply type	Non Dimmable
Emergency	No