

# FLOS

SA.1008.5E110 Raw

## USO 2200 Cove Lighting



Recessed soft ceiling luminaire. Direct lighting with LED lamps. See LED drivers.

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

### Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
LED type	LED Module
Lamp category	LED
Number of lamps	50
Power (W)	3.6
System power (W)	180
Source flux (lm)	18750

### Physical

Colour	Raw
Trim	No
Orientation	Fixed
Recessed depth (mm)	210
Length (mm)	2700
Net weight (kg)	165
IP internal	20



### Download

[Mounting instructions](#) PDF

[Mounting instructions](#) PDF

### Photometric Files


[LDT / IES](#) ZIP

### Technical Drawings


[3D](#) ZIP



### Ecodesign and Energy Labelling



## Schematic light drawing



Beam Angle: 138°

h(m)	E(lx)	D(m)
1	986	5.23
2	247	10.45
3	110	15.68
4	62	20.90
5	39	26.13

## Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
Beam angle C0-180 (°)	138
Beam angle C90-270 (°)	138
Extreme cut off	No
UGR <sub>L</sub>	<16

## Electrical

Forward voltage (V)	24
Power supply	Remote excluded
Dimmable	No

## Notes

Delivered in two pieces.

---

## Accessories & Power Supply



REQUIRED  
Power supply

Electrical

60.8268

LED power supply source for remote installation in 24V/240W electric control panel. 100/240V



REQUIRED  
Power supply

Electrical

60.9352

LED power supply source for remote installation in 24V/200W electric control panel. To avoid problems of overload it is recommended to install a power source every 185W. 100/240V.



OPTIONAL  
Accessory

Electrical

06.1016.00

Wiring 500mm for white module




OPTIONAL  
Accessory

Electrical

08.8297.00

2 Meters Prolongation Cable for white modules




OPTIONAL  
Power supply

Electrical

06.1019.00E

DALI Master Interface Dimmable White



OPTIONAL  
Power supply

Electrical

06.1020.00E

White DALI, DMX & RF Slave Interface Dimmable




OPTIONAL  
Power supply

Electrical

60.9658

White&RGB Casambi Wireless Dimmable Interface



OPTIONAL  
Control interface

Electrical

06.1022.00E

Dimmable Interface. 1-10V interface with two 500mm feed cable for white LED modules with fast connection