

09.7315.40A90 White

## UT Pro 175 GA-69

Designed by FLOS Architectural, 2017




35.3W - 3221lm - 4000K - CRI> 90 - Beam° 24

The UT Spot is a family of high output indoor track light suitable for any application, from museum exhibitions to commercial premises and offices or residential environments. The UT pro 175 serie is an exclusive projector, which combined with an integrated electronic driver within the body of the luminaire, creates a minimal visual impact. The optical housing of the luminaire is manufactured in high-pressure injected aluminum, with white or black finishes. UT PRO 175 is available with Spot, Medium and Flood optics.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Track               |
| Environments           | Indoor dry location |
| Light Source Type      | LED                 |
| Light sources included | Yes                 |
| LED type               | LED array           |
| Number of lamps        | 1                   |
| Power (W)              | 35.3                |
| Source flux (lm)       | 3674                |
| System flux (lm)       | 3221                |

### Physical

|                          |            |
|--------------------------|------------|
| Color                    | White      |
| Orientation              | Adjustable |
| Rotation (°)             | 360        |
| Longitudinal tilting (°) | 90         |
| Length (in)              | 2.96       |
| Net weight (lb)          | 2.18       |
| Package volume (in)      | 428        |
| IP internal              | 20         |

### Download

|                       |                     |
|-----------------------|---------------------|
| Family spec sheet     | <a href="#">ZIP</a> |
| Mounting instructions | <a href="#">PDF</a> |

### Photometric Files


|           |                     |
|-----------|---------------------|
| LDT / IES | <a href="#">ZIP</a> |
|-----------|---------------------|

### Technical Drawings

|    |                     |
|----|---------------------|
| 2D | <a href="#">ZIP</a> |
| 3D | <a href="#">ZIP</a> |



Schematic light drawing



Photometric

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| Light distribution     | Symmetric |
| CCT (K)                | 4000      |
| CRI>                   | 90        |
| Beam angle C0-180 (°)  | 24        |
| Beam angle C90-270 (°) | 24        |
| Extreme cut off        | No        |
| UGRL                   | <10       |

Electrical

|                     |            |
|---------------------|------------|
| Insulation class    | I          |
| Frequency (Hz)      | 60         |
| Main voltage (Vac)  | 120-277    |
| Forward voltage (V) | 37.6       |
| LED current (mA)    | 940        |
| Driver              | Integrated |

Notes

Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time.

Accessories & Power Supply



OPTIONAL  
Accessory

ACCESSORYTYPE4

08.9107.00

Honeycomb

OPTIONAL  
Accessory

ACCESSORYTYPE4

08.9108.00

Screening Crosspiece

OPTIONAL  
Accessory

ACCESSORYTYPE4

08.9109.00

Elliptical lens

OPTIONAL  
Accessory

ACCESSORYTYPE4

08.9110.00

Flood Lens