

09.7317.40A90 White

UT Pro 175 GA-69

Designed by FLOS Architectural, 2017




LED - LED array - 3000K - Beam° 34

The UT Spot is a family of high output indoor track light suitable for any application, from museum exhibitions to commercial premises and offices or residential environments. The UT pro 175 serie is an exclusive projector, which combined with an integrated electronic driver within the body of the luminaire, creates a minimal visual impact. The optical housing of the luminaire is manufactured in high-pressure injected aluminum, with white or black finishes. UT PRO 175 is available with Spot, Medium and Flood optics.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

Mounting	Track
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	LED array
Lamp category	LED
Number of lamps	1
System power (W)	35.3

Physical

Color	White
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	90
Length (in)	2.96
Net weight (lb)	2.18
Package volume (in)	428
IP internal	20

Download

Family spec sheet	ZIP
Mounting instructions	PDF

Photometric Files

LDT / IES	ZIP
-----------	---------------------

Technical Drawings


2D	ZIP
3D	ZIP



Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class G

Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
Beam angle C0-180 (°)	34
Beam angle C90-270 (°)	34
UGRL	<19

Electrical

Insulation class	I
Frequency (Hz)	60
Main voltage (Vac)	120-277
Forward voltage (V)	37.6
LED current (mA)	940
Driver	Integrated
Dimmable	No
Dimming type	Non Dimmable

Notes

Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time.