

FLOS

09.7318.14A Black

UT Pro 175 GA-69 On Board Dimmer

UPGRADE


Designed by FLOS Architectural, 2017



Spotlight to be installed in standard 3-phase track with LED light source. 120-270V power supply integrated. High performance reflector included.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Track
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	LED array
Lamp category	LED
Number of lamps	1
Power (W)	35.3
System power (W)	46.5
Source flux (lm)	4278
Lumen Output (lm)	3137

Physical

Colour	Black
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	90
Spot diameter (mm)	75
Net weight (kg)	0.99
IP internal	20

Download

Mounting instructions [↓ PDF](#)

Photometric Files

LDT / IES [↓ ZIP](#)


Technical Drawings

2D [↓ ZIP](#)

3D [↓ ZIP](#)



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	4000
CRI>	90
Beam angle C0-180 (°)	34
Beam angle C90-270 (°)	34
UGR _L	<19

Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Forward voltage (V)	37.6
LED current (mA)	940
Power supply	Integrated
Dimmable	Yes
Power supply type	Dimmer on board
Dimming range (%)	10-100
Dimming interface	Dimmer Integrated

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class G



Notes

Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time.