

FLOS

09.4472.14A9S Black

UT Spot Ceiling Ø 57


Designed by FLOS Architectural, 2017



The UT Spot is a family of high output indoor lights suitable for any application, from museum exhibitions to commercial premises and offices or residential environments. A light fixture for indoor use to be mounted on ceilings, available in LED technology light sources and in ELV&FF or 1-10V dimming versions.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Ceiling surface, Wall surface
Environments	Indoor dry location
Light Source Type	LED
LED type	LED array
Lamp category	LED
Number of lamps	1
Power (W)	18
Source flux (lm)	2179.6
System flux (lm)	1216

Physical

Color	Black
Trim	Yes
Rotation (°)	360
Longitudinal tilting (°)	90
Spot diameter (in)	2.25
Net weight (lb)	1.31
Package volume (in)	428
IP internal	20

Download

Family spec sheet	ZIP
Mounting instructions	PDF

Photometric Files


LDT / IES	ZIP
-----------	-----

Technical Drawings

2D	ZIP
3D	ZIP



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	4000
CRI>	90
Beam angle C0-180 (°)	42
Beam angle C90-270 (°)	42
UGR _L	<16

Electrical

Insulation class	III
Forward voltage (V)	36.7
LED current (mA)	450
Driver	Remote excluded

Notes

Integral LED is not field replaceable. IC-rated downlight for direct insulation contact. Fixture is constant Current Low Volatge LED, Class 2. Just 1 accessory can be install at the time. For filter options contact Flos. Semi recessed Spotlight, Wiring suitable for plenum spaces 3500K available, but not ataloged. Consult factory for additional color temperatures.

Accessories & Power Supply




REQUIRED
Power supply
Electrical

SP25W450MA-10V-A02
Splice Box UL 7"x3-5/8"x1-1/4"
450mA 25W 0-10V



REQUIRED
Power supply
Electrical

SP40W450MA-10V-A02
Splice Box UL 7"x3-5/8"x1-1/4"
450mA 40W 0-10V



REQUIRED
Housing and Hanger Bar
TRAY-0017

Registration Tray - non electrical,
place holder for non IC new
construction, UT57 Trim Ø3.56"




OPTIONAL
Accessory
Optical

08.0526.00
Snoot shielding cone



OPTIONAL
Accessory
Optical

08.8428.00
Honeycomb



OPTIONAL
Accessory
Optical

08.8429.00
Screening crosspiece



OPTIONAL
Accessory
Optical

08.8431.00
Elliptical lens



OPTIONAL
Accessory
Optical

08.8432.00
Flood lens



OPTIONAL
Accessory

Optical

08.0526.40

Snoot shielding cone