



09.4483.14A9V Black

UT Spot Track Ø 57
Designed by FLOS Architectural, 2017




LED - LED array - 18W - 1033lm - 4000K - CRI> 90 - Beam° 21

Spotlight to be installed on 3-phase track. with LED light source. 120V, 60Hz ELV power supply integrated.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Track
Environments	Indoor dry location
Light Source Type	LED
LED type	LED array
Lamp category	LED
Number of lamps	1
Power (W)	18
Source flux (lm)	2275
System flux (lm)	1033

Physical

Color	Black
Rotation (°)	360
Longitudinal tilting (°)	90
Net weight (lb)	1.26
Package height (in)	#VALUE!
Package width (in)	#VALUE!
Package length (in)	#VALUE!
Package volume (in)	428
IP internal	20

Download

- Family spec sheet [ZIP](#)
- Mounting instructions [PDF](#)

Photometric Files


- LDT / IES [ZIP](#)

Technical Drawings

- 2D [ZIP](#)
- 3D [ZIP](#)



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	4000
CRI>	90
Beam angle C0-180 (°)	21
Beam angle C90-270 (°)	21
UGRL	<10

Electrical

Insulation class	II
Frequency (Hz)	60
Main voltage (Vac)	120
LED current (mA)	500
Driver	Integrated
Dimmable	Yes
Dimming type	Mains Cut Dimming

Notes

Screening crosspiece, lenses and Honeycomb directly installable on the head of the luminaire without needing any fastening accessory. FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request..

Class 2

Accessories & Power Supply



OPTIONAL
Accessory

ACCESSORYTYPE4

08.0526.00

Snoot shielding cone




OPTIONAL
Accessory

ACCESSORYTYPE4

08.8428.00

Honeycomb



OPTIONAL
Accessory

ACCESSORYTYPE4

08.8429.00

Screening crosspiece



OPTIONAL
Accessory

ACCESSORYTYPE4

08.8431.00

Elliptical lens



OPTIONAL
Accessory

ACCESSORYTYPE4

08.8432.00

Flood lens



OPTIONAL
Accessory

ACCESSORYTYPE4

08.0526.40

Snoot shielding cone