

FLOS


09.4880.30A9V White

UT Spot Track Ø 86

Designed by FLOS Architectural, 2017

LED - LED array - 33W - 2650lm - 3000K - CRI> 80 - Beam° 12

The UT Spot is a family of high output indoor track lights suitable for any application, from museum exhibitions to commercial premises and offices or residential environments. Available up to 3770 lumens each, the UT Spot is line voltage and houses its driver in a discreet small box that integrates with the track, giving it a sleek modern look. A luminaire for indoor use to be mounted on three phase track, available in LED technology light sources and in dimmable or not dimmable versions. The optical housing of the luminaire is manufactured in high-pressure injected aluminum, with white or black finishes.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Track
Environments	Indoor dry location
Light Source Type	LED
LED type	LED array
Lamp category	LED
Number of lamps	1
Power (W)	33
Source flux (lm)	3959
System flux (lm)	2650

Physical

Color	White
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	90
Spot diameter (in)	3.3899999999999997
Net weight (lb)	1.65
Gross weight (lb)	2.15
Package volume (in)	428
IP internal	20

Download

Family spec sheet	ZIP
Mounting instructions	PDF

Photometric Files


LDT / IES	ZIP
-----------	---------------------

Technical Drawings

2D	ZIP
3D	ZIP



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	80
Beam angle C0-180 (°)	12
Beam angle C90-270 (°)	12
UGRL	<10

Electrical

Insulation class	II
Frequency (Hz)	60
Main voltage (Vac)	120
LED current (mA)	900
Driver	Integrated
Dimmable	Yes
Dimming type	Mains Cut Dimming

Notes

FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request.

Accessories & Power Supply



OPTIONAL
Accessory

ACCESSORYTYPE4

08.8410.00

Holding ring



OPTIONAL
Accessory

ACCESSORYTYPE4

08.8411.00

Screening crosspiece



OPTIONAL
Accessory

ACCESSORYTYPE4

08.8163.68

Elliptical lens



OPTIONAL
Accessory

ACCESSORYTYPE4

08.8175.68

Flood lens



OPTIONAL
Accessory

ACCESSORYTYPE4

08.8495.14

Honeycomb