

# FLOS


09.4883.14A9V Black

## UT Spot Track Ø 86

Designed by FLOS Architectural, 2017

LED - LED array - 33W - 2176lm - 4000K - CRI> 90 - Beam° 24

The UT Spot is a family of high output indoor track lights suitable for any application, from museum exhibitions to commercial premises and offices or residential environments. Available up to 3770 lumens each, the UT Spot is line voltage and houses its driver in a discreet small box that integrates with the track, giving it a sleek modern look. A luminaire for indoor use to be mounted on three phase track, available in LED technology light sources and in dimmable or not dimmable versions. The optical housing of the luminaire is manufactured in high-pressure injected aluminum, with white or black finishes.



Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

### Main specifications

|                   |                     |
|-------------------|---------------------|
| Mounting          | Track               |
| Environments      | Indoor dry location |
| Light Source Type | LED                 |
| LED type          | LED array           |
| Lamp category     | LED                 |
| Number of lamps   | 1                   |
| Power (W)         | 33                  |
| Source flux (lm)  | 3506                |
| System flux (lm)  | 2176                |

### Physical

|                          |                    |
|--------------------------|--------------------|
| Color                    | Black              |
| Orientation              | Adjustable         |
| Rotation (°)             | 360                |
| Longitudinal tilting (°) | 90                 |
| Spot diameter (in)       | 3.3899999999999997 |
| Net weight (lb)          | 1.65               |
| Gross weight (lb)        | 2.15               |
| Package volume (in)      | 428                |
| IP internal              | 20                 |

### Download

|                       |     |
|-----------------------|-----|
| Family spec sheet     | ZIP |
| Mounting instructions | PDF |

### Photometric Files


|           |     |
|-----------|-----|
| LDT / IES | ZIP |
|-----------|-----|

### Technical Drawings

|    |     |
|----|-----|
| 2D | ZIP |
| 3D | ZIP |



Schematic light drawing



Photometric

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| Light distribution     | Symmetric |
| CCT (K)                | 4000      |
| CRI>                   | 90        |
| Beam angle C0-180 (°)  | 24        |
| Beam angle C90-270 (°) | 24        |
| UGRL                   | <10       |

Electrical

|                    |                   |
|--------------------|-------------------|
| Insulation class   | II                |
| Frequency (Hz)     | 60                |
| Main voltage (Vac) | 120               |
| LED current (mA)   | 900               |
| Driver             | Integrated        |
| Dimmable           | Yes               |
| Dimming type       | Mains Cut Dimming |

Notes

FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request.

Accessories & Power Supply



OPTIONAL  
Accessory

ACCESSORYTYPE4

08.8410.00

Holding ring



OPTIONAL  
Accessory

ACCESSORYTYPE4

08.8411.00

Screening crosspiece



OPTIONAL  
Accessory

ACCESSORYTYPE4

08.8163.68

Elliptical lens



OPTIONAL  
Accessory

ACCESSORYTYPE4

08.8175.68

Flood lens



OPTIONAL  
Accessory

ACCESSORYTYPE4

08.8495.14

Honeycomb