

FLOS

09.4984.14.90 Black


UT Spot Track Multichip Ø 86

Designed by FLOS Architectural, 2016



LED - Top LED - 11.5W - 687lm - 3000K - CRI> 90 - Beam° 8

The UT Spot is a family of high output indoor track lights suitable for any application, from museum exhibitions to commercial premises and offices or residential environments. Available up to 3770 lumens each, the UT Spot is line voltage and houses its driver in a discreet small box that integrates with the track, giving it a sleek modern look. A luminaire for indoor use to be mounted on three phase track, available in LED technology light sources and in dimmable or not dimmable versions. The optical housing of the luminaire is manufactured in high-pressure injected aluminum, with white or black finishes.



Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

Main specifications

Mounting	Track
Environments	Indoor dry location
Light Source Type	LED
LED type	Top LED
Lamp category	LED
Number of lamps	1
Power (W)	11.5
Source flux (lm)	838.15
System flux (lm)	687

Physical

Color	Black
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	90
Spot diameter (in)	3.3899999999999997
Net weight (lb)	2.61
Package volume (in)	428
IP internal	20

Download

Family spec sheet	ZIP
Mounting instructions	PDF

Photometric Files


LDT / IES	ZIP
-----------	-----

Technical Drawings

2D	ZIP
3D	ZIP



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
Beam angle C0-180 (°)	8
Beam angle C90-270 (°)	8
UGRL	<10

Electrical

Insulation class	II
Frequency (Hz)	60
Main voltage (Vac)	120-277
LED current (mA)	1050
Driver	Integrated
Dimmable	No
Dimming type	Non Dimmable

Notes

FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request.