

## Walkstick Pipe 1 H 600 mm Non Dimmable


Designed by Antonio Citterio, 2019



220-240V power supply included. Ready for installation on solid surface. Box for ground installation to be ordered separately. Included 2 way terminal block 4 poles IP68 H2O Stop. Version 110V upon request.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



### Main specifications

|                        |               |
|------------------------|---------------|
| EAN                    | 8054793207315 |
| Mounting               | Ground        |
| Light source type      | LED           |
| Light sources included | Yes           |
| LED type               | Power LED     |
| Number of lamps        | 1             |
| Power (W)              | 7             |
| System power (W)       | 7             |
| Lumen Output (lm)      | 483           |

### Physical

|                     |            |
|---------------------|------------|
| Colour              | Anthracite |
| Trim                | No         |
| Orientation         | Adjustable |
| Net weight (kg)     | 1.8        |
| Package height (mm) | 671        |
| Package width (mm)  | 260        |
| Package length (mm) | 185        |
| Package volume (m3) | 0.03       |
| IP internal         | 65         |
| Drive Over          | No         |

### Download

Mounting instructions [Download PDF](#)

### Photometric Files


|           |                              |
|-----------|------------------------------|
| LDT / IES | <a href="#">Download ZIP</a> |
| LDT / IES | <a href="#">Download ZIP</a> |
| LDT / IES | <a href="#">Download ZIP</a> |
| LDT / IES | <a href="#">Download ZIP</a> |

### Technical Drawings

|     |                              |
|-----|------------------------------|
| 2D  | <a href="#">Download ZIP</a> |
| 3D  | <a href="#">Download ZIP</a> |
| Bim | <a href="#">Download ZIP</a> |



Schematic light drawing



Photometric

|                        |            |
|------------------------|------------|
| Lighting type          | Direct     |
| Light distribution     | Asymmetric |
| CCT (K)                | 2700       |
| CRI>                   | 80         |
| Beam angle C0-180 (°)  | 97         |
| Beam angle C90-270 (°) | 97         |

Electrical

|                    |              |
|--------------------|--------------|
| Insulation class   | II           |
| Frequency (Hz)     | 50/60        |
| Main voltage (Vac) | 220-240      |
| Power supply       | Integrated   |
| Dimmable           | No           |
| Power supply type  | Non Dimmable |
| Dimming interface  | Not Dimmable |
| Emergency          | No           |

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class D

Replaceable (LED only) light source by a professional

Replaceable control gear by a professional

Notes

Ready for installation on solid surface. Box for ground installation to be ordered separately. Included 2 way terminal block 4 poles IP68 H2O Stop. Version 110V upon request.


Accessories & Power Supply



OPTIONAL  
Accessory

F001Z020000

Box for ground installation



OPTIONAL  
Accessory

F990E00A000

S.P.D. (SURGE PROTECTION  
DEVICE)