

# FLOS

03.8090.40 White

## Wallee On Board Dimmer

Designed by Niels Bendtsen, 2017



Lighting LED module to be installed in The Tracking Magnet System.

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

### Main specifications

Mounting	Track
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Top LED
Lamp category	LED
Power (W)	10
System power (W)	9.3
Source flux (lm)	722
Lumen Output (lm)	413
Efficacy (lm/W)	44.41

### Physical

Colour	White
Trim	No
Orientation	Adjustable
Rotation (°)	25
Longitudinal tilting (°)	25
Length (mm)	242
Net weight (kg)	0.22
IP internal	20
IP external	20



### Download

[Mounting instructions](#)  PDF

### Photometric Files

[LDT / IES](#)  ZIP

### Technical Drawings


[2D](#)  ZIP

[3D](#)  ZIP

[Bim](#)  ZIP



## Schematic light drawing



## Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
McAdam steps (SDCM)	2
LED Life / Failure Ratio	L80B50 > 50.000h (Tc=85°C)
Beam angle C0-180 (°)	100
Beam angle C90-270 (°)	100

## Electrical

Insulation class	III
Forward voltage (V)	48
LED current (mA)	190
Power supply	Remote excluded
Dimmable	Yes
Power supply type	Dimmer on board
Dimming range (%)	20-100
Dimming interface	Dimmer Integrated
Emergency	No

## Notes

When installing Wallee, it may require a manual adjustment by the client/installer. Find information on how to carry out this adjustment in the instruction sheets. Only allowed with Tracking Magnet Recessed and horizontal installation.

## Ecodesign and Energy

### Labelling

