

## Workmates In-Track Large High Efficiency Dali

Designed by FLOS Architectural, 2023



22W - 2790lm - 4000K - CRI> 90 - Beam° 67

Luminaire for use on a three-phase track, with adapters for No Dim and Dali control. High-efficiency light source. Also available in a The Running Magnet version. This can rotate by 360° on the axis of its rear arm to reach any position relative to the track (from parallel to perpendicular). UGR<19. EN12464 - cd/m2 @ 65°<3000 compliant.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Track               |
| Environments           | Indoor dry location |
| Light source type      | LED                 |
| Light sources included | yes                 |
| LED type               | Top LED             |
| Number of lamps        | 1                   |
| Power (W)              | 22                  |
| Source flux (lm)       | 3080                |
| Lumen Output (lm)      | 2790                |

### Physical

|                 |           |
|-----------------|-----------|
| Colour          | All White |
| Net weight (kg) | 0.86      |
| IP internal     | 20        |



### Download

Mounting instructions



### Photometric Files

LDT / IES



### Technical Drawings


2D



3D



Schematic light drawing



Photometric

|                          |                  |
|--------------------------|------------------|
| Lighting type            | Direct           |
| Light distribution       | Symmetric        |
| CCT (K)                  | 4000             |
| CRI>                     | 90               |
| Rf fidelity index        | 89               |
| Rg gamut index           | 98               |
| LED Life / Failure Ratio | L80B10 > 50.000h |
| Beam angle C0-180 (°)    | 67               |
| Beam angle C90-270 (°)   | 67               |
| Extreme cut off          | No               |
| UGRL                     | <16              |

Electrical

|                    |                                       |
|--------------------|---------------------------------------|
| Insulation class   | II                                    |
| Frequency (Hz)     | 50/60                                 |
| Main voltage (Vac) | 220-240                               |
| LED current (mA)   | 500                                   |
| Power supply       | Integrated                            |
| Dimmable           | Yes                                   |
| Power supply type  | Dimmable DALI 2                       |
| Dimming interface  | Remote Dimmable (Dimmer Not Included) |

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class G

Replaceable (LED only) light source by a professional

Replaceable control gear by a professional