

Workmates In-Track Small Full Spectrum Non Dimmable

Designed by FLOS Architectural, 2023



15.5W - 1182lm - 3500K - CRI> 98 - Beam° 66

Luminaire for use on a three-phase track, with adapters for No Dim and Dali control. High-efficiency light source. Also available in a The Running Magnet version. This can rotate by 360° on the axis of its rear arm to reach any position relative to the track (from parallel to perpendicular). UGR<19. EN12464 - cd/m2 @ 65°<3000 compliant.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Track
Environments	Indoor dry location
Light source type	LED
Light sources included	yes
LED type	Top LED
Number of lamps	1
Power (W)	15.5
Source flux (lm)	1518
Lumen Output (lm)	1182

Physical

Colour	Black
Net weight (kg)	0.63
IP internal	20



Download

Mounting instructions [Download PDF](#)

Photometric Files

LDT / IES [Download ZIP](#)


Technical Drawings

2D [Download ZIP](#)

3D [Download ZIP](#)



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3500
CRI>	98
Rf fidelity index	97
Rg gamut index	101
LED Life / Failure Ratio	L80B10 > 50.000h
Beam angle C0-180 (°)	66
Beam angle C90-270 (°)	65
Extreme cut off	No
UGRL	<16

Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
LED current (mA)	350
Power supply	Integrated
Dimmable	No
Power supply type	Non Dimmable
Dimming interface	Not Dimmable

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class G

Replaceable (LED only) light source by a professional

Replaceable control gear by a professional