

## Workmates Track Large High Efficiency

Designed by FLOS Architectural, 2023



Luminaire for use on The Running Magnet system. High-efficiency light source. This can rotate by 360° on the axis of its rear arm to reach any position relative to the track (from parallel to perpendicular). UGR<19. EN12464 - cd/m<sup>2</sup> @ 65°<3000 compliant. Casambi, máximo distance between fixtures: 50m.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

### Main specifications

|                  |                     |
|------------------|---------------------|
| Mounting         | Track               |
| Environments     | Indoor dry location |
| LED type         | Top LED             |
| Number of lamps  | 1                   |
| Power (W)        | 13.5                |
| Source flux (lm) | 1682                |
| System flux (lm) | 1386                |

### Physical

|              |       |
|--------------|-------|
| Color        | White |
| Orientation  | Fixed |
| Rotation (°) | 360   |
| Length (in)  | 388   |
| IP internal  | 20    |



### Download

- Family spec sheet
- Mounting instructions
- ZIP
- PDF

### Photometric Files


- LDT / IES
- ZIP

### Technical Drawings

- 2D
- 3D
- ZIP
- ZIP



Schematic light drawing



Photometric

|                          |                       |
|--------------------------|-----------------------|
| Lighting type            | Direct                |
| Light distribution       | Symmetric             |
| CCT (K)                  | 3000                  |
| CRI>                     | 90                    |
| Rf fidelity index        | 87                    |
| Rg gamut index           | 103                   |
| LED Life / Failure Ratio | L80B50>60.000h_Tc85°C |
| Beam angle C0-180 (°)    | 66                    |
| Beam angle C90-270 (°)   | 65                    |
| Extreme cut off          | Yes                   |
| UGR <sub>L</sub>         | <16                   |

Electrical

|                     |                                       |
|---------------------|---------------------------------------|
| Insulation class    | III                                   |
| Main voltage (Vac)  | 24                                    |
| Forward voltage (V) | 12                                    |
| LED current (mA)    | 900                                   |
| Driver              | Remote                                |
| Dimmable            | Yes                                   |
| Dimming type        | Dimmable DALI 2                       |
| Dimming interface   | Remote Dimmable (Dimmer Not Included) |

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class G

Replaceable (LED only) light source by a professional

Replaceable control gear by a professional

Notes

Before placing your order, please consult the product details also on the catalogue, in its technical data sheet and in the installation and assembly instructions to find all the information that may not be included in this site or that could be relevant to your specific project or installation.