

FLOS

05.6431.AP Aluminized Silver

Workmates Track Small Full Spectrum Non Dimmable

Designed by FLOS Architectural, 2023



Luminaire for use on The Running Magnet system. High-quality colour rendering Full Spectrum light source. This can rotate by 360° on the axis of its rear arm to reach any position relative to the track (from parallel to perpendicular). UGR<19. EN12464 - cd/m² @ 65°<3000 compliant. Casambi, maximum distance between fixtures: 50m.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

| | |
|------------------------|---------------------|
| Mounting | Track |
| Environments | Indoor dry location |
| Light source type | LED |
| Light sources included | Yes |
| LED type | Top LED |
| Lamp category | LED |
| Number of lamps | 1 |
| Power (W) | 10 |
| System power (W) | 10 |
| Source flux (lm) | 942 |
| Lumen Output (lm) | 711 |
| Efficacy (lm/W) | 71 |

Physical

| | |
|-----------------|-------------------|
| Colour | Aluminized Silver |
| Orientation | Fixed |
| Rotation (°) | 360 |
| Net weight (kg) | 0.6 |
| IP internal | 20 |
| IP external | 20 |

Download

Mounting instructions [↓ PDF](#)

Photometric Files

LDT / IES [↓ ZIP](#)


Technical Drawings

2D [↓ ZIP](#)

3D [↓ ZIP](#)



Schematic light drawing



Photometric

| | |
|--------------------------|-----------------------|
| Lighting type | Direct |
| Light distribution | Symmetric |
| CCT (K) | 3500 |
| CRI> | 98 |
| McAdam steps (SDCM) | 3 |
| Rf fidelity index | 97 |
| Rg gamut index | 102 |
| LED Life / Failure Ratio | L80B50>60.000h_Tc85°C |
| Beam angle C0-180 (°) | 75 |
| Beam angle C90-270 (°) | 75 |
| Extreme cut off | Yes |
| UGR _L | <16 |

Electrical

| | |
|---------------------|--------------|
| Insulation class | III |
| Forward voltage (V) | 24 |
| LED current (mA) | 700 |
| Power supply | Remote |
| Dimmable | No |
| Power supply type | Non Dimmable |
| Dimming interface | Not Dimmable |

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F



Notes

Before placing your order, please consult the product details also on the catalogue, in its technical data sheet and in the installation and assembly instructions to find all the information that may not be included in this site or that could be relevant to your specific project or installation.