


X Connector Feed Non Dimmable

Designed by FLOS Architectural, 2023



Wall surface, Ceiling surface

Cross-shaped connector. Can be powered via connections on the back. Rear feeding cable entry.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Wall surface, Ceiling surface
Environments	Indoor dry location
Light sources included	No

Physical

Color	Brushed Bronze
IP internal	20



Download

Family spec sheet	ZIP
Mounting instructions	PDF



Photometric

Extreme cut off	No
-----------------	----

Electrical

Insulation class	III
Forward voltage (V)	24
Driver	Remote excluded
Dimmable	No
Dimming type	Non Dimmable

Accessories & Power Supply



REQUIRED
Power supply


Electrical

LEDSB60W24V-NDM-D01
LED Driver, 24VDC, 60W, Non-Dimming, 120-277V



REQUIRED
Power supply


LEDSB96W24V-NDM-D01
LED Driver, 24VDC, 96W, Non-Dimming, 120-277V



OPTIONAL
Power supply

Electrical


08.0613.14A
Dimmable control box 1-10V, 24/48V. For remote installation.



OPTIONAL
Component

Installation

06.2618.40A
Track Cover 3000mm



OPTIONAL
Component

Installation

06.2618.14A
Track Cover 3000mm



OPTIONAL
Connector

Electrical

06.2608.14
Straight Connector