


# FLOS

06.2616.ES Brushed Bronze

## X Connector Feed Non Dimmable

Designed by FLOS Architectural, 2023




Wall surface, Ceiling surface

Cross-shaped connector. Can be powered via connections on the back. Rear feeding cable entry.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

Mounting Wall surface, Ceiling surface

Environments Indoor dry location

Light sources included No

### Physical

Colour Brushed Bronze

Net weight (kg) 0.03

IP internal 20

### Download

[Mounting instructions](#)

[PDF](#)



### Photometric

Extreme cut off No

### Electrical

Insulation class III

Forward voltage (V) 24

Power supply Remote excluded

Dimmable No

Power supply type Non Dimmable

## Accessories & Power Supply



REQUIRED  
Power supply

Electrical

60.9352

LED power supply source for remote installation in 24V/200W electric control panel. To avoid problems of overload it is recommended to install a power source every 185W. 100/240V.



REQUIRED  
Power supply

Electrical

60.9777A

Remote Power Supply Non Dimmable 24V. 120W. 220/240V




REQUIRED  
Power supply

Electrical

60.9705A

Remote Power Supply Non Dimmable 24V. 60W. 220/240V




OPTIONAL  
Power supply

Electrical

08.0613.14A

Dimmable control box 1-10V, 24/48V. For remote installation.




OPTIONAL  
Component

Installation

06.2618.40A

Track Cover 3000mm



OPTIONAL  
Component

Installation

06.2618.14A

Track Cover 3000mm



OPTIONAL  
Connector

Electrical

06.2608.14

Straight Connector