

**Dali 2 Continuous current power supply of 1-32W, 110/240V - 50/60Hz with power current selected through adjustable 250 mA - 12W / 300 mA - 14W / 350 mA - 17W / 400 mA - 19W / 450 mA - 22W / 500 mA - 24W / 550 mA - 26W / 600 mA - 28W / 650 mA - 31W / 7...**



Continuous current power supply of 1-32W, 110\*/240V - 50/60Hz with power current selected through adjustable 250 mA - 12W / 300 mA - 14W / 350 mA - 17W / 400 mA - 19W / 450 mA - 22W / 500 mA - 24W / 550 mA - 26W / 600 mA - 28W / 650 mA - 31W / 700 mA - 32W, Dali 2 switch. \*110V = Max. 15W

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications


Environments	Indoor dry location
Power (W)	32

Physical

Length (mm)	103
Net weight (kg)	0.14
IP internal	20



Ecodesign and Energy Labelling



Replaceable control gear by a professional

Photometric

Extreme cut off                      No

Electrical

Frequency (Hz)	50/60
Main voltage (Vac)	110-240
Forward voltage (V)	48
LED current (mA)	250 - 300 - 350 - 400 - 450 - 500 - 550 - 600 - 650 - 700
Power supply	Remote
Dimmable	Yes
Power supply type	Dimmable DALI 2
Dimming range (%)	1-100
Dimming interface	Remote Dimmable (Dimmer Not Included)
Emergency	Yes
Batteries inside	No