

FLOS

FA53000756 Matte Stainless Steel


A-Rise 130 NEW

Designed by FLOS Outdoor



3.5W - 199lm - 4000K - CRI> 80 - Beam° 120

Mains voltage LED light source included. Requires a junction box to be ordered separately. The luminaire is equipped with a protruding, neoprene, 250 mm cable with an integrated 2-way, 3-pole H2O STOP connection system guaranteeing the water tightness of the connection. Frosted glass.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Ground recessed, Wall recessed, Floor recessed
Environment	Outdoor wet location
LED type	Power LED
Number of heads	1
Power (W)	3.5
System power (W)	4
Source flux (lm)	400
System flux (lm)	199

Physical

Colour	Matte Stainless Steel
Orientation	Fixed
IP internal	66/67

Download

Mounting instructions [↓ ZIP](#)

Photometric Files

LDT / IES [↓ ZIP](#)

Technical Drawings

2D [↓ ZIP](#)

3D [↓ ZIP](#)




Ecodesign and Energy Labelling



Non-replaceable light source

Schematic light drawing



Beam Angle: 120°

h(m)	E(lx)	D(m)
1	54	3.49
2	13	6.98
3	6	10.48
4	3	13.97
5	2	17.46

Luminous flux Luminaire
199 lm

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	4000
CRI>	80
Beam angle C0-180 (°)	120
Beam angle C90-270 (°)	120

Electrical

Insulation class	I
Frequency (Hz)	50-60
Main voltage (Vac)	220-230
Driver	Integrated
Dimmable	No
Dimming type	Non Dimmable
Emergency type	No

Accessories & Power Supply



REQUIRED
Accessory

FA50


Box for Installation A-Rise 130



OPTIONAL
Accessory

F990C010000

3/4 way terminal block 4 poles
IP68 H2O stop. (ø5,5÷12mm
cable)



OPTIONAL
Accessory

F990E00A000

S.P.D. (SURGE PROTECTION
DEVICE)