

# FLOS

FA53000556 Matte Stainless Steel


## A-Rise 130 HP Low Voltage NEW

Designed by FLOS Outdoor, 2012



7W - 394lm - 4000K - CRI> 80 - Beam° 96

LED light source included. 24V remote electric power supply to be ordered separately, ON/OFF and adjustable light intensity from 1 to 10V or DALI. Requires a junction box to be ordered separately. The luminaire is equipped with a protruding, neoprene, 250 mm cable with an integrated H2O STOP connection system and a wiring kit with crimp connectors and adhesive heat-shrink tubing guaranteeing the water tightness of the connection. Frosted glass.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

### Main specifications

EAN	8054793649740
Mounting	In-ground
Environments	Outdoor wet location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
Power (W)	7
System power (W)	7.3
Source flux (lm)	734
Lumen Output (lm)	394

### Physical

Colour	Matte Stainless Steel
Orientation	Fixed
Net weight (kg)	0.46
Package height (mm)	95
Package width (mm)	140
Package length (mm)	140
IP internal	67
IP external	66


### Download

[Mounting instructions](#)  ZIP

### Photometric Files

[LDT / IES](#)  ZIP

### Technical Drawings

[2D](#)  ZIP

[3D](#)  ZIP


### Ecodesign and Energy Labelling



Non-replaceable light source



Schematic light drawing



Photometric

Light distribution	Symmetric
CCT (K)	4000
CRI>	80
Beam angle C0-180 (°)	96
Beam angle C90-270 (°)	96
Extreme cut off	No

Electrical

Insulation class	III
Frequency (Hz)	50/60
Main voltage (Vac)	24
Power supply	Remote excluded
Power supply type	Dimmable
Emergency	No

Accessories & Power Supply



REQUIRED  
Accessory

FA50  
Box for Installation A-Rise 130



OPTIONAL  
Accessory

F990C050000  
2 way terminal block 2 poles IP68  
H2O stop. (Ø4÷6,9mm cable)



OPTIONAL  
Power supply

F990B27A000  
Power supply 24Vdc 70W / 220-  
240V IP67 Class I selv. Non  
Dimmable



OPTIONAL  
Power supply

F990B28A000  
Power supply 24Vdc 50W / 220-  
240V IP67 Class I selv. Non  
Dimmable



OPTIONAL  
Power supply

F990B29A000  
Power supply 24Vdc 100W /  
220-240V IP67 Class I selv.Non  
Dimmable



OPTIONAL  
Power supply

RF25747  
Power supply 24V 10W /110-  
240V IP20 Class II selv. Non  
Dimmable



OPTIONAL  
Power supply

RF25750  
Power supply 24Vdc 17W / 110-  
240V (15W@110V) IP20 Class II  
selv. Dimmable Push-Dimm Or  
1.10V



OPTIONAL  
Power supply

F990B21A000  
Power supply 17W/110÷240V  
-24Vdc (15W@110V) IP67 Class  
II Selv. Dimmable Push-Dimm Or  
1.10V



OPTIONAL  
Power supply

RF25757

Power supply 24V 10W / 110-  
240V IP67 Class II selv.\_Non  
Dimmable



OPTIONAL  
Power supply

RF25752

Power supply 24Vdc 20W / 220-  
240V IP67 Class II selv. Non  
Dimmable



OPTIONAL  
Power supply

F990B23AZ00

Power supply 24Vdc 35W /120-  
270V IP67 Class II selv.